

HUMMEL products are available from MARYLAND METRICS

P.O.Box 261 Owings Mills, MD 21117 USA

phones: (410)358-3130 (800)638-1830 faxes: (410)358-3142 (800)872-9329

email: sales@mdmetric.com web: <http://mdmetric.com>



Setting Standards

Assembly Tools

Special tools to facilitate efficient and quick assembly of HSK liquid tight strain relief fittings.

ST

Socket wrench for efficient strain relief fittings assembly.

It encloses the dome nut on five sides, eliminating cross threading.

RS


The ratched wrench allows fast and reliable strain relief fitting assembly.

It encloses the dome nut on five sides, eliminating cross threading. The ratchet head fits standard torque wrenches.

US

Universal strap wrench for efficient and quick strain relief fitting assembly.






Tool for efficient and safe assembly of the HSK strain relief fittings

Socket wrench

mm	L mm	C mm	D mm	Number
14	60	9	19	1.500.1400.04
15	60	9,5	20	1.500.1500.04
17	60	10	23,5	1.500.1700.04
19	60	11	26	1.500.1900.04
20	60	12	27	1.500.2000.04
22	60	13	29,5	1.500.2200.04
24	60	15	32,5	1.500.2400.04
27	60	17	35,5	1.500.2700.04
30	60	18	40,5	1.500.3000.04
33	60	20	43,5	1.500.3300.04
36	60	22	47,5	1.500.3600.04
40	100	25	52,5	1.500.4000.04
41	100	27	53,5	1.500.4100.04
42	100	27	54,5	1.500.4200.04
46	100	31	60	1.500.4600.04
50	100	32	65,5	1.500.5000.04
53	100	32	71,5	1.500.5300.04
55	100	32	72	1.500.5500.04
57	100	36	75,5	1.500.5700.04
60	100	38	78,5	1.500.6000.04
64	100	40	84	1.500.6400.04
65	100	42	85	1.500.6500.04
68	100	42	87	1.500.6800.04





Tool for efficient and safe assembly of the HSK strain relief fittings

Slit Ratchet Wrench and Accessories

mm	Number
Ratchet head	1.501.0100.00
Ratchet grip	1.501.0200.00
Hex inserts	
14	1.501.1400.04
15	1.501.1500.04
17	1.501.1700.04
19	1.501.1900.04
20	1.501.2000.04
22	1.501.2200.04
24	1.501.2400.04
27	1.501.2700.04
30 *	1.501.3000.04

* Max. cable diameter = 17 mm

